

Pipe and sewer cleaning nozzles – The full portfolio

All nozzles can be supplied with various nozzle heads, nozzle extensions as well as adjustable slides, with and without propulsive nozzles available. This allows for thorough cleaning of pipes and sewers with different diameters.

Cleaning nozzle **DFK 55**

The robust nozzle for sewer cleaning – also suited for narrow pipes.

DFK 55	
Allowed operating pressure	50–1,600 bar
Recommended flow rate	25–150 l/min
Rotational speed range	100–1,500 min ⁻¹
Minimum diameter (with smallest slide)	67 mm
Minimum diameter (without slide)	55 mm



Cleaning nozzle **DFK 61**

The leakage-free pipe cleaning nozzle with adjustable rotational speed for maximum pressure.

DFK 61	
Allowed operating pressure	1,600–3,000 bar
Recommended flow rate	10–40 l/min
Rotational speed range	500–2,000 min ⁻¹
Minimum diameter (with smallest slide)	75 mm
Minimum diameter (without slide)	61 mm



Cleaning nozzle **DFK 90**

The all-rounder amongst the rotating sewer cleaning nozzles for high flow rate capacity.

DFK 90	
Allowed operating pressure	50–800 bar
Recommended flow rate	30–400 l/min
Rotational speed range	200–1,200 min ⁻¹
Minimum diameter (with smallest slide)	145 mm
Minimum diameter (without slide)	90 mm




All-purpose pipe and sewer cleaning nozzles



Individually drilled, reversible



Individually drilled, reversible




Bombs and grenades

Extra and special nozzles



Rod Nozzles



Flounder



Bulldozer



Bulldog



Root cutter, cutting chain



Rotation nozzle

Nozzle inserts

All nozzles are available in various diameters and for different pressure levels. Nozzle inserts for various pressure levels and flow rates are also available.



Type R



Type E



Type L



Type P



Type N